



NOTES:
 1. PUMPING UNIT INLET THREADS ARE M10-1.5 X 12MM DEEP ON 3.06 BOLT CIRCLE PATTERN (3 PLACES)
 2. PUMPING UNIT MOUNTING THREADS ARE M8-1.25 X THROUGH (4 PLACE).
 3. METER MOUNTING HOLES ARE ON 4.12 BOLT CIRCLE.
 4. PUMPING UNIT PULLEY IS FOR USE WITH 4L SECTION 1/2" BELT
 5. PUMPING UNIT TO OPERATE BETWEEN 650 AND 700 RPM
 6. PULLEY HAS 6" OUTSIDE DIAMETER.
 7. DIMENSIONS SHOWN ARE THEORETICAL DIMENSIONS AND SUBJECT TO CASTING/MACHINING VARIATIONS
 8. SOME OPTIONS WILL CHANGE SOME DIMENSIONS. CONTACT FACTORY FOR CLEARANCE FIT DIAGRAM FOR PUMPING UNIT AND OPTIONS DESIRED.

OPTIONS AVAILABLE FROM FACTORY:
 1. HEAVY DUTY OR STANDARD DUTY PUMPING UNIT.
 2. ADJUSTABLE BYPASS.
 3. OIML COMPLIANT AIR SEPARATION
 4. PAPER FILTER, STRAINER OR STRAINER WITH SACK FILTRATION
 5. ATMOSPHERIC VENT FLDAT.
 6. STANDARD FUELS OR ALCOHOL FUELS.
 7. STEPPED PULLEY
 8. OPTIONAL PUMP COVERS AND OUTLET MANIFOLDS
 9. INLET CHECK VALVE.
 10. INLET CASTING FOR CONNECTING TO 1 1/2" NPT.
 CONSULT FACTORY FOR SPECIFIC PART NUMBER WHEN OPTIONS HAVE BEEN DECIDED.