

Bennett 3000 SERIES



SPECIFICATIONS

DIMENSIONS	Low Hose: 30" w x 60" h x 20" d High Hose: 30" w x 88" h* x 20" d
PRODUCTS	Up to 2 products (per side)
HOSES	Up to 2 Hoses (per side)
UNIT TYPE	Straight Grade Only
HYDRAULICS	Suction or Remote
VOLTAGE	115/230 VAC, 50/60Hz
FLOW RATE	40/90/140/260 lpm
INLET / OUTLET	3.8cm dia NPT / 2.54cm dia NPT
PROTOCOL	Bennett Open Protocol / RS485

DISPLAYS

SALES DISPLAY	LCD 6-Digit 1" (2.54cm) Numbers
VOLUME DISPLAY	LCD 6-Digit 1" (2.54cm) Numbers
PRICE PER UD	LCD 4-Digit ½" (1.27cm) Numbers
BACKLIGHT	LED Backlight - Low Power Consumption
TOTALIZERS	7-Digit Electro-Mechanical Totalizer 1 Per Hose Electronic Non-Resettable Totals 8.3 for Volume and 9.2 for Money

OPTIONS

PAYMENT	<ul style="list-style-type: none"> • Local Preset • 3rd Party POS Integration • PCI Compliant / EMV Card Readers*
MERCHANDISING DISPLAYS	<ul style="list-style-type: none"> • 5.7in High Resolution Color Display • 7in High Resolution Widescreen Color Display
ADDITIONAL OPTIONS	<ul style="list-style-type: none"> • Stainless Steel • Front or Side Mount Nozzle Boots

*Fuel Dispenser EMV Compliance Note: Additional software and hardware will be required for full EMV compliance.