

# 3000 SERIES



**Bennett**  
simply better

# 3000 SERIES SPECIFICATIONS

## STANDARD FEATURES

**Dimensions:** Low Hose: 30" w x 60" h x 20" d  
High Hose: 30" w x 88" h x 20" d

**Products:** Up to 2 Products (per side)

**Hoses:** Up to 2 Hoses (per side)

**Unit Type:** Straight Grade Only

**Hydraulics:** Suction or Remote

**Activation:** Lift to Start

**Displays:** LCD 8-Digit 1" for Sales and Volume  
LCD 4-Digit ½" Price Per Volume

**Voltage:** 120/240 VAC, 50/60Hz

**Flow Rate:** 18-23GPM<sup>1</sup>

**Inlet / Outlet:** 1.5" dia NPT / 1" dia NPT

**Protocol:** Bennett Open Protocol / Generic / RS485

**Regulatory:** UL™ Listed, Weights and Measures



## OPTIONAL FEATURES

**Payment Options<sup>2</sup>:** A variety of payment options are available for the 3000 series dispenser depending on your needs.

- EMV-R: 7 Widescreen display with soft keys, Hybrid Chip EMV Card Reader, PCI Compliant EMV ready EPP, High Speed Receipt Printer
- Full-EMV: Full EMV payment with 7" Display (require dispenser hub board and in-store hub box)
- Credit-Alpha: 7" Widescreen display with soft keys, Dual Side Credit/Fleet Card Reader, Alphanumeric Pin-Pad, High Speed Receipt Printer
- Credit-Numeric: Numeric Credit Only Payment
- Audio: Media Kit with External Audio for 7" Displays
- NFC
- Local Preset

**Stainless Steel:** Optional stainless steel packages for doors, end panels, top cover, electronic cover assembly, hinged upper doors and grade panel area

**Other Options:** Low Hose or High Hose, Side Mount or Front Mount Nozzle Boots, Two-Tier Price Displays, Electro-Mechanical Totalizers, Junction Box, Pulse Output Board, Automatic Temperature Compensation, Intercom Speaker, Intercom Speaker with Call Button, Custom Graphics, Valance (high hose models)

## BASE MODEL NUMBER DESCRIPTIONS

1	2	3	4	5	6	7
3	8	1	2	S	N	R

1. **3000 Dispenser Series:** Always "3"
2. **Display Type:** 7=Commercial Display | 8=Retail Display 1 Tier Prices | 9=Retail Display Two Price Tiers
3. **Products:** 1 or 2
4. **Hose Outlets:** 1, 2, or 4
5. **Flow Rate:** S=Standard
6. **Hydraulic Details:** Always N for None
7. **Hydraulics:** R=Remote | S=Suction | P=Suction w/ Prepay Valve(s)

<sup>1</sup> Flow rates are nominal rates under test conditions. Actual rates will vary subject to installation conditions, hanging hardware used, and submerged pump used if applicable.

<sup>2</sup> Payment options are only available on Front Mounted Units

**Bennett**  
simply better